<u>Bold and single underline</u>: new language since preliminary adoption <u>Bold, strikeout and single underline</u>: new language being stricken since preliminary adoption and proposed rule as printed

TITLE 329 IAC SOLID WASTE MANAGEMENT BOARD

PROPOSED RULE FOR FINAL ADOPTION WITH IDEM'S SUGGESTED CHANGES INCORPORATED

DIGEST

Amends 329 IAC 4.1, concerning regulation of wastes containing PCBs, to readopt for the purposes of IC 13-14-9.5 and amend to update the incorporation by reference of the Code of Federal Regulations, update the viewing/copying location and addresses, clarify public notice requirements, remove the language relating to manifests to reflect the current statute, simplify certain notifications, and update disposal options. Effective 30 days after filing with the Indiana Register.

HISTORY

First Notice of Comment Period: September 1, 2005, Indiana Register (28 IR 3689).

Second Notice of Comment Period and Notice of First Hearing: December 1, 2005, Indiana Register (29 IR 1055).

Date of First Hearing: March 21, 2006.

Proposed Rule and Notice of Third Comment Period and Second Hearing: May 1, 2006, Indiana Register (29 IR 2639).

Date of Second Hearing: July 18, 2006.

329 IAC 4.1-1-1	329 IAC 4.1-6-2
329 IAC 4.1-1-2	329 IAC 4.1-7-1
329 IAC 4.1-1-3	329 IAC 4.1-7-2
329 IAC 4.1-1-4	329 IAC 4.1-7-3
329 IAC 4.1-1-5	329 IAC 4.1-7-4
329 IAC 4.1-1-6	329 IAC 4.1-7-5
329 IAC 4.1-2-1	329 IAC 4.1-8-1
329 IAC 4.1-2-2	329 IAC 4.1-8-2
329 IAC 4.1-2-3	329 IAC 4.1-8-3
329 IAC 4.1-2-4	329 IAC 4.1-8-4
329 IAC 4.1-2-5	329 IAC 4.1-8-5
329 IAC 4.1-2-6	329 IAC 4.1-9-1
329 IAC 4.1-2-7	329 IAC 4.1-9-2
329 IAC 4.1-2-8	329 IAC 4.1-9-3
329 IAC 4.1-2-9	329 IAC 4.1-9-4
329 IAC 4.1-3-1	329 IAC 4.1-9-5
329 IAC 4.1-4-1	329 IAC 4.1-10-1
329 IAC 4.1-4-2	329 IAC 4.1-11-1
329 IAC 4.1-5-1	329 IAC 4.1-11-2
329 IAC 4.1-5-2	329 IAC 4.1-11-3
329 IAC 4.1-6-1	

329 IAC 4.1-11-4 329 IAC 4.1-12-1 329 IAC 4.1-13-1 329 IAC 4.1-13-2 329 IAC 4.1-13-3 329 IAC 4.1-13-4 329 IAC 4.1-13-5

SECTION 1. 329 IAC 4.1-1-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-1-1 Applicability

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 1. This article applies to a person who disposes of **any** solid or liquid waste containing PCBs. (Solid Waste Management Board; 329 IAC 4.1-1-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3073)

SECTION 2. 329 IAC 4.1-1-2 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-1-2 Enforcement

Authority: IC 13-20-15-1

Affected: IC 13-14-2-6; IC 13-20-15-6; IC 13-30-3

Sec. 2. This article is **shall be** enforced under IC 13-14-2-6 or IC 13-30-3, or both. No date contained in the federal regulations incorporated by reference in this article shall be construed to allow or require retroactive enforcement of this article. (Solid Waste Management Board; 329 IAC 4.1-1-2; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3073)

SECTION 3. 329 IAC 4.1-1-3 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-1-3 Penalties

Authority: IC 13-20-15-1; IC 13-20-15-7

Affected: IC 13-20-15-6

Sec. 3. Penalties for violations a violation of this article are listed in IC 13-20-15-7. (Solid Waste Management Board; 329 IAC 4.1-1-3; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3073)

SECTION 4. 329 IAC 4.1-1-4 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-1-4 Variances

Authority: IC 13-14-8-8; IC 13-20-15-1

Affected: IC 13-20-15-6

Sec. 4. The commissioner may grant a variance from compliance with the provisions a provision of this article in accordance with IC 13-14-8-8. (Solid Waste Management Board; 329 IAC 4.1-1-4; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3074)

SECTION 5. 329 IAC 4.1-1-5 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-1-5 Dilution

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 5. No person may avoid any provision **of this article** specifying a PCB concentration by diluting the PCBs unless otherwise specifically provided. (Solid Waste Management Board; 329 IAC 4.1-1-5; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3074)

SECTION 6. 329 IAC 4.1-1-6 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-1-6 Incorporation by reference

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 6. (a) When incorporated by reference in this article, references to 40 CFR 264 and 40 CFR 761 shall mean the version of that publication revised as of July 1, 1999. **2003.**
- (b) Sales of the Code of Federal Regulations are handled by the Superintendent of Documents, U.S. Government Printing Office, 732 North Capitol Street NW, Washington, D.C. 20402. 20401. The telephone number for the U.S. Government Printing Office is (202) 512-1800. (202) 512-0000. The incorporated materials are available for public review at the Indiana Department of Environmental Management, Office of Solid and Hazardous Waste Management, Land Quality, Indiana Government Center-North, 100 North Senate Avenue, Eleventh Floor West, Indianapolis, Indiana.
- (c) Table 1 shows documents referenced in 40 CFR 761 and the updated versions of those documents that must be used to comply with this article.

	Table 1.	
Version Referenced in 40 CFR 761	Version to be Used	Source
40 CFR 136 as amended in 41 FR	40 CFR 136, revised as of July 1, 1999	1
52779 on December 1, 1976		
"Thermal Processing and Land	40 CFR 240, revised as of July 1, 1999;	1
Disposal of Solid Waste" (39 FR	40 CFR 257, revised as of July 1, 1999;	
29337, Aug. 14, 1974)	and	
	40 CFR 258, revised as of July 1, 1999	
U.S. Department of Transportation	49 CFR 172, revised as of October 1,	1
(DOT) or U.S. Postal Service (USPS)	1999	
shipping requirements, found		
respectively in 49 CFR 173.345 and		
U.S. Postal Regulations 652.2 and		
652.3		
ASTM Standard D93-90	ASTM Standard D93-99	2

ASTM Standard D129-64 ASTM Standard D240-87 ASTM Standard D240-87 ASTM Standard E258-67 (Reapproved 1987) ASTM Standard D482-87 ASTM Standard D482-87 ASTM Standard D482-87 ASTM Standard D524-88 ASTM Standard D524-97 ASTM Standard D923-88 ASTM Standard D923-86 or ASTM Standard D923-89 ASTM Standard D1266-87 ASTM Standard D1266-87 ASTM Standard D1266-87 ASTM Standard D1796-83 (Reapproved 1990) ASTM Standard D2158-89 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2784-89 ASTM Standard D3178-84 ASTM Standard D3178-89 ASTM Standard D3178-89 ASTM Standard D3178-89 ASTM Standard D3278-89 ASTM Standard D3278-96 □ Visual Standard No. 2; Near-White Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) □ □Visual Standard No. 3; Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) □ □Visual Standard No. 3; Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) □ □Visual Standard No. 3; Commercial Blast Cleaning Standard No. 3 (Pormore National Association of Corrosion Engineers (NACE) □ □Visual Standard No. 3; Commercial Blast Cleaning Standard No. 3 (Pormore National Association of Corrosion Engineers (NACE) □ □Visual Standard No. 3; Commercial Blast Cleaning Approved October 1994 □ □ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□			
ASTM Standard E258-67 (Reapproved 1987) ASTM Standard D482-87 ASTM Standard D524-88 ASTM Standard D524-88 ASTM Standard D923-86 or ASTM Standard D923-89 ASTM Standard D1266-87 ASTM Standard D1266-87 ASTM Standard D1266-87 ASTM Standard D1266-88 ASTM Standard D1266-98 ASTM Standard D278-96 Visual Standard D278-89 ASTM Standard D3178-89 (Reapproved 1997) ASTM Standard D4059-96 Visual Standard D4059-96 Visual Standard No. 2, Near-White Blast Cleaning D126-97 ASTM Standard D4059-96 Visual Standard No. 3; Commercial D126-98 ASTM Standard D4059-96 Visual Standard No. 3; Commercial D126-98 ASTM Standard D4059-96 Visual Standard No. 3; Commercial D1266-98 ASTM Standard D4059-96 Visual Standard No. 3; Commercial D1266-98 ASTM Standard D4059-96 Visual Standard No. 3; Commercial D1266-98 ASTM Standard D4059-96 Visual Standard No. 3; Commercial D1266-98 NACE No. 3/SSPC-SP 6 "Commercial D1266-98 NACE No. 3/SSPC-SP 6 "C	ASTM Standard D129-64	ASTM Standard D129-95	2
(Reapproved 1987) ASTM Standard D482-87 ASTM Standard D524-88 ASTM Standard D6524-88 ASTM Standard D808-87 ASTM Standard D923-86 or ASTM Standard D923-89 ASTM Standard D1266-87 ASTM Standard D1266-87 ASTM Standard D1266-87 ASTM Standard D1796-83 (Reapproved 1990) ASTM Standard D2158-89 ASTM Standard D2158-89 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2784-89 ASTM Standard D3278-89 ASTM Standard D3278-89 ASTM Standard D3278-89 ASTM Standard D4059 "Visual Standard No: 2, Near-White Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Visual Standard No: 3, Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Standard D4059 "Standard No: 3, Commercial Blast Cleaning ", Approved October 1994 "NACE No: 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October 1994	ASTM Standard D240-87	\ 11	2
ASTM Standard D524-88 ASTM Standard D808-87 ASTM Standard D923-86 or ASTM Standard D923-89 ASTM Standard D1266-87 ASTM Standard D1796-83 (Reapproved 1990) ASTM Standard D2158-89 ASTM Standard D2158-89 ASTM Standard D2158-89 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2784-89 ASTM Standard D2784-89 ASTM Standard D3178-84 ASTM Standard D3178-89 ASTM Standard D3178-89 ASTM Standard D3278-96 ASTM Standard D3278-96 STM			2
ASTM Standard D808-87 ASTM Standard D923-86 or ASTM Standard D923-97 Standard D923-89 ASTM Standard D1266-87 ASTM Standard D1266-87 ASTM Standard D1796-83 (Reapproved 1990) ASTM Standard D2158-89 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2784-89 ASTM Standard D2784-89 ASTM Standard D3178-84 ASTM Standard D3178-89 (Reapproved 1997) ASTM Standard D3278-89 ASTM Standard D3278-89 ASTM Standard D3278-96 2 ASTM Standard D4059 Wisual Standard No. 2, Near-White Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaning Standard D3178-89 (Commercial D3278-96 Commercial D3278-96 Commercial Blast Cleaning Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning Standard NACE No. 3/SSPC-SP 6 Commercial Blast Cleaning Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning Approved October 1994	ASTM Standard D482-87	ASTM Standard D482-95	2
ASTM Standard D923-86 or ASTM Standard D923-97 ASTM Standard D1266-87 ASTM Standard D1796-83 (Reapproved 1990) ASTM Standard D2158-89 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2709-96€1 2 ASTM Standard D2784-89 ASTM Standard D3178-84 ASTM Standard D3178-89 ASTM Standard D3278-96€1 2 ASTM Standard D3278-96€1 2 ASTM Standard D3278-96€1 2 ASTM Standard D3278-96€1 2 ASTM Standard D4059 ASTM Standard D4059-96 2 "Visual Standard No. 2, Near-White National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Dint Surface Preparation Standard Nace No. 2/SSPC-SP 10 "Near-White National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Dint Surface Preparation Standard Nace No. 3/SSPC-SP 6 "Commercial Dint Surface Preparation Standard Nace No. 3/SSPC-SP 6 "Commercial Dint Surface Preparation Standard Nace No. 3/SSPC-SP 6 "Commercial Dint Surface Preparation Standard Nace No. 3/SSPC-SP 6 "Commercial Dint Surface Preparation Standard Nace No. 3/SSPC-SP 6 "Commercial Dint Surface Preparation Standard Nace No. 3/SSPC-SP 6 "Commercial Dint Surface Preparation Standard Nace No. 3/SSPC-SP 6 "Commercial Dint Surface Preparation Standard Nace No. 3/SSPC-SP 6 "Commercial Dint Surface Preparation Standard Nace No. 3/SSPC-SP 6 "Commercial Dint Surface Preparation Standard Nace No. 3/SSPC-SP 6 "Commercial Dint Surface Preparation Standard Nace Nace Nace Preparation Standard Nace Preparation Standard Nace Nace Preparation Standard Nace Prepar	ASTM Standard D524-88	ASTM Standard D524-97	2
ASTM Standard D1266-87 ASTM Standard D1796-83 (Reapproved 1990) ASTM Standard D2158-89 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2784-89 ASTM Standard D3178-84 ASTM Standard D3178-84 ASTM Standard D3178-89 ASTM Standard D3178-89 ASTM Standard D3278-89 ASTM Standard D3278-89 ASTM Standard D3278-89 ASTM Standard D3278-96 ASTM Standard D4059 "Visual Standard No. 2, Near-White Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaning", Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning", Approved October Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaning", Approved October Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaning", Approved October Engineers (NACE)	ASTM Standard D808-87	ASTM Standard D808-95	2
ASTM Standard D1266-87 ASTM Standard D1796-83 (Reapproved 1990) ASTM Standard D2158-89 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2784-89 ASTM Standard D2784-89 ASTM Standard D3178-84 ASTM Standard D3178-89 ASTM Standard D3178-89 ASTM Standard D3178-89 ASTM Standard D3278-89 ASTM Standard D3278-89 ASTM Standard D3278-96 "Visual Standard No. 2, Near-White National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Dlast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) Blast Cleaning Tandard D4059 "Visual Standard No. 3, Commercial D4059-96 "Visual Standard No. 3,	ASTM Standard D923-86 or ASTM	ASTM Standard D923-97	2
ASTM Standard D1796-83 (Reapproved 1990) ASTM Standard D2158-89 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2709-96 2 ASTM Standard D3178-84 ASTM Standard D3178-89 (Reapproved 1997) ASTM Standard D3178-84 ASTM Standard D3178-89 (Reapproved 1997) ASTM Standard D3278-89 ASTM Standard D3278-96 2 ASTM Standard D4059 ASTM Standard D4059-96 2 "Visual Standard No. 2, Near-White Blast Cleaned Surface Finish", of the NACE No. 2/SSPC-SP 10 "Near-White National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaning", Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning", Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning", Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning", Approved October 1994	Standard D923-89		
(Reapproved 1990) ASTM Standard D2158-89 ASTM Standard D2709-88 ASTM Standard D2709-88 ASTM Standard D2784-89 ASTM Standard D3178-84 ASTM Standard D3178-89 (Reapproved 1997) ASTM Standard D3278-89 ASTM Standard D3278-96 ASTM Standard D3278-96 ASTM Standard D4059 ASTM Standard D4059 ASTM Standard D4059 ASTM Standard D4059-96 Wisual Standard No. 2, Near-White National Association of Corrosion Engineers (NACE) Wisual Standard No. 3, Commercial Dinit Surface Preparation Standard Details Cleaning Approved October 1994 Wisual Standard No. 3, Commercial Dinit Surface Preparation Standard NACE No. 3/SSPC-SP 6 "Commercial Dast Cleaning", Approved October Engineers (NACE) Wisual Standard No. 3, Commercial Dinit Surface Preparation Standard NACE No. 3/SSPC-SP 6 "Commercial Dast Cleaning", Approved October Engineers (NACE) Blast Cleaning", Approved October 1994	ASTM Standard D1266-87	ASTM Standard D1266-98	2
ASTM Standard D2158-89 ASTM Standard D2709-88 ASTM Standard D2784-89 ASTM Standard D2784-89 ASTM Standard D3178-84 ASTM Standard D3178-89 (Reapproved 1997) ASTM Standard D3278-89 ASTM Standard D3278-89 ASTM Standard D3278-96 ASTM Standard D4059 ASTM Standard D4059 ASTM Standard D4059 ASTM Standard D4059-96 2 Wisual Standard No. 2, Near-White Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) Wisual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the NACE No. 3/SSPC-SP 6 "Commercial National Association of Corrosion Engineers (NACE) Blast Cleaning", Approved October Engineers (NACE) Blast Cleaning", Approved October Engineers (NACE)	ASTM Standard D1796-83	ASTM Standard D1796-97	2
ASTM Standard D2709-88 ASTM Standard D2784-89 ASTM Standard D3178-84 ASTM Standard D3178-89 (Reapproved 1997) ASTM Standard D3278-89 ASTM Standard D3278-89 ASTM Standard D3278-96 2 ASTM Standard D4059 "Visual Standard No. 2, Near-White Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the NACE No. 2/SSPC-SP 10 "Near-White National Association of Corrosion Blast Cleaning", Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning", Approved October 1994 Blast Cleaned Surface Finish", of the NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October 1994 NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October 1994	(Reapproved 1990)		
ASTM Standard D2784-89 ASTM Standard D3178-84 ASTM Standard D3178-89 (Reapproved 1997) ASTM Standard D3278-89 ASTM Standard D3278-96 2 ASTM Standard D4059 ASTM Standard D4059-96 2 "Visual Standard No. 2, Near-White National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the NACE No. 3/SSPC-SP 6 "Commercial NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October 1994 NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October Blast Cleaning", Approved October 1994	ASTM Standard D2158-89	ASTM Standard D2158-97	2
ASTM Standard D3178-84 ASTM Standard D3278-89 (Reapproved 1997) ASTM Standard D3278-96 2 ASTM Standard D4059 ASTM Standard D4059-96 2 "Visual Standard No. 2, Near-White Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaning", Approved October 1994 "Visual Standard No. 3, Commercial Blast Cleaning", Approved October 1994 "ASTM Standard D3278-96 2 ASTM Standard D4059-96 2 ASTM Standard D4059-96 2 Joint Surface Preparation Standard October 1994 "Visual Standard No. 3, Commercial Blast Cleaning", Approved October NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October 1994 Blast Cleaning", Approved October 1994	ASTM Standard D2709-88	ASTM Standard D2709-96 ^{€1}	2
ASTM Standard D3278-89 ASTM Standard D4059 "Visual Standard No. 2, Near-White Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Blast Cleaned Surface Finish", of the NACE No. 2/SSPC-SP 10 "Near-White October 1994 "Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) Blast Cleaning", Approved October Blast Cleaning", Approved October 1994	ASTM Standard D2784-89	ASTM Standard D2784-98	2
ASTM Standard D4059 "Visual Standard No. 2, Near-White Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) ASTM Standard D4059-96 Joint Surface Preparation Standard October 1994 Joint Surface Preparation Standard NACE No. 3/SSPC-SP 6 "Commercial NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October 1994	ASTM Standard D3178-84	\ 11	2
"Visual Standard No. 2, Near-White Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) Joint Surface Preparation Standard October 1994 Joint Surface Preparation Standard No. 3, Surface Preparation Standard Standard No. 3, Commercial Blast Cleaning", Approved October Habitation of Corrosion Blast Cleaning", Approved October 1994	ASTM Standard D3278-89	ASTM Standard D3278-96 ^{€1}	2
Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) Blast Cleaning", Approved NACE No. 3/SSPC-SP 6 "Commercial NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October Engineers (NACE) 1994	ASTM Standard D4059	ASTM Standard D4059-96	2
National Association of Corrosion Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) Metal Blast Cleaning", Approved October 1994 Joint Surface Preparation Standard NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October 1994	"Visual Standard No. 2, Near-White	Joint Surface Preparation Standard	3
Engineers (NACE) "Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) October 1994 Joint Surface Preparation Standard NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October 1994	Blast Cleaned Surface Finish", of the	NACE No. 2/SSPC-SP 10 "Near-White	
"Visual Standard No. 3, Commercial Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) Joint Surface Preparation Standard NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October 1994	National Association of Corrosion		
Blast Cleaned Surface Finish", of the National Association of Corrosion Engineers (NACE) NACE No. 3/SSPC-SP 6 "Commercial Blast Cleaning", Approved October 1994	Engineers (NACE)	October 1994	
National Association of Corrosion Engineers (NACE) Blast Cleaning", Approved October 1994	, and the second se	<u>*</u>	3
Engineers (NACE) 1994	·		
	, ,		

Source 1: Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402, telephone (202) 512-1800.

Source 2: American Society for Testing and Materials, Customer Services, 100 Barr Harbor Drive, West Conshohocken, Pennsylvania 19428-2959, telephone (610) 832-9555.

Source 3: NACE International, P.O. Box 218340, Houston, Texas 77218-8340, telephone (281) 228-6200; or Steel Structures Painting Council, 4516 Henry Street, Suite 301, Pittsburgh, Pennsylvania 15213-3728, telephone (412) 687-1113.

(d) Table 2 shows documents referenced in 40 CFR 761 with no specified edition and provides the date of the edition that must be used to comply with this article.

Table 2.

Document Referenced in 40 CFR

761 Edition to be Used Source

SW-846 or "Test Methods for Evaluating Solid Waste, Physical Chemical Methods", U.S. Environmental Protection Agency Publication SW-846	Third Edition (November 1986), as amended by Updates I (July 1992), II (September 1994), IIA (August 1993), IIB (January 1995), and III (December 1996)	1
Occupational Safety and Health Standards, 29 CFR 1910.106, Flammable and combustible liquids	Revised as of July 1, 1999	1
40 CFR 60 (referred to as part 60 of this chapter)	Revised as of July 1, 1999	1
40 CFR 112 (referred to as part 112 of this title)	Revised as of July 1, 1999	1
40 CFR 112.1(d)(2)	Revised as of July 1, 1999	1
40 CFR 112.4	Revised as of July 1, 1999	1
40 CFR 122 (referred to as part 122 of	Revised as of July 1, 1999	1
this chapter)	• ,	
40 CFR 264.143 (referred to as	Revised as of July 1, 1999	1
section 264.143 of this chapter)	• ,	
40 CFR 264.151 (referred to as	Revised as of July 1, 1999	1
section 264.151 of this chapter)	• •	
40 CFR 264.175 (referred to as	Revised as of July 1, 1999	1
section 264.175 of this chapter)	• •	
40 CFR 266, Subpart H (referred to as	Revised as of July 1, 1999	1
part 266, subpart H of this chapter)	•	
40 CFR 270.66 (referred to as section	Revised as of July 1, 1999	1
270.66 of this chapter)		
DOT Hazardous Materials Regulations at 49 CFR parts 171 through 180	Revised as of October 1, 1999	1
49 CFR Chapter I, Subchapter C	Revised as of September 30, 1991	1
49 CFR 171.14	Revised as of October 1, 1999	1
"Verification of PCB Spill Cleanup by	"Verification of PCB Spill Cleanup	2
Sampling and Analysis", Midwest	by Sampling and Analysis", U.S.	_
Research Institute	Environmental Protection Agency Publication EPA-560/5-85-026, August 1985	
"Field Manual for Grid Sampling of	"Field Manual for Grid Sampling of	2
PCB Spill Sites to Verify Cleanup",	PCB Spill Sites to Verify Cleanup",	
Midwest Research Institute	U.S. Environmental Protection Agency Publication EPA-560/5-86- 017, May 1986	
	017, 1viay 1700	

"Wipe Sampling and Double Wash/Rinse Cleanup as Recommended by the Environmental Protection Agency PCB Spill Cleanup Policy", dated June 23, 1987 and revised on April 18, 1991

"Wipe Sampling and Double
Wash/Rinse Cleanup as
Recommended by the Environmental
Protection Agency PCB Spill Cleanup
Policy", June 23, 1987, revised and
clarified on April 18, 1991

2

Source 1: Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402, telephone (202) 512-1800.

Source 2: TSCA Technical Information Service, Environmental Protection Agency, 401 M Street, SW, Washington, D.C. 20460, telephone (202) 554-1404.

(c) If not specified in the federal regulations incorporated by reference, the version of materials incorporated by reference in those federal regulations is the version that was in effect on the effective date of the 2006 amendments to this rule. (Solid Waste Management Board; 329 IAC 4.1-1-6; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3074)

SECTION 7. 329 IAC 4.1-2-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-2-1 Applicability; incorporation by reference

Authority: IC 13-20-15-1

Affected: IC 13-11-2; IC 13-20-15-6

- Sec. 1. (a) The definitions in IC 13-11-2 and this rule apply to this article. In addition to the definitions in IC 13-11-2, the definitions in this rule apply throughout this article.
- (b) The definitions at 40 CFR 761.3 are incorporated by reference, except as provided otherwise in section 2 of this rule.
- (c) 40 CFR 761.3 is available for viewing and copying at the Indiana Department of Environmental Management, Office of Solid and Hazardous Waste Management, Land Quality, Indiana Government Center-North, 100 North Senate Avenue, Eleventh Floor West, Indianapolis, Indiana.
- (d) The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, 732 North Capitol Street NW, Washington, D.C. 20402. 20401. The telephone number for the Superintendent of Documents U.S. Government Printing Office is (202) 512-1800. (202) 512-0000. (Solid Waste Management Board; 329 IAC 4.1-2-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3075)

SECTION 8. 329 IAC 4.1-2-2 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-2-2 Exceptions and additions

Authority: IC 13-20-15-1

Affected: IC 13-11-2-155; IC 13-11-2-158; IC 13-20-15-6

Sec. 2. Exceptions and additions to the definitions **contained** in 40 CFR 761.3 are as follows: (1) Delete the definition of "person" and substitute the definition at IC 13-11-2-158(a).

(2) Delete the definition of "PCB and PCBs" and substitute the definition of PCB at IC 13-11-2-155.

(Solid Waste Management Board; 329 IAC 4.1-2-2; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3075)

SECTION 9. 329 IAC 4.1-2-3 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-2-3 "Alternative disposal facility" defined

Authority: IC 13-20-15-1 IC 13-20-15-6

Sec. 3. (a) "Alternative disposal facility" means a facility that:

- (1) separates;
- (2) processes;
- (3) recovers;
- (4) treats;
- (5) transfers; or
- (6) disposes of;

PCB waste. and

- (2) is not one (1) of (b) The term does not include the following:
- (A) (1) A chemical waste landfill.
- (B) (2) An incinerator.
- (C) (3) A high efficiency boiler.
- (D) (4) A mobile facility.
- (E) (5) A generator of PCB waste.
- (c) An alternative disposal facility is provides an alternative method of destroying PCBs as described in 40 CFR 761.60(e). (Solid Waste Management Board; 329 IAC 4.1-2-3; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3075)

SECTION 10. 329 IAC 4.1-2-4 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-2-4 "EPA" defined

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 4. "EPA" means the United States federal Environmental Protection Agency. (Solid Waste Management Board; 329 IAC 4.1-2-4; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3075)

SECTION 11. 329 IAC 4.1-2-5 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-2-5 "Mobile facility" defined

Authority: IC 13-20-15-1 IC 13-20-15-6

Sec. 5. "Mobile facility" means machinery, equipment, or vehicles of any nature that are used or intended to be used at more than one (1) location for the:

- (1) separation;
- (2) processing;
- (3) recovery, as defined at 329 IAC 10-2-149; or
- (4) treatment;

of PCBs in a material or waste containing PCBs. (Solid Waste Management Board; 329 IAC 4.1-2-5; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3076)

SECTION 12. 329 IAC 4.1-2-6 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-2-6 "Municipal solid waste landfill" or "MSWLF" defined

Authority: IC 13-20-15-1 IC 13-20-15-6

Sec. 6. "Municipal solid waste landfill" or "MSWLF" has the meaning as set forth at in 329 IAC 10-2-116. (Solid Waste Management Board; 329 IAC 4.1-2-6; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3076)

SECTION 13. 329 IAC 4.1-2-7 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-2-7 "Municipal solid waste landfill unit" or "MSWLF unit" defined

Authority: IC 13-20-15-1 IC 13-20-15-6

Sec. 7. "Municipal solid waste landfill unit" or "MSWLF unit" has the meaning as set forth at in 329 IAC 10-2-117. (Solid Waste Management Board; 329 IAC 4.1-2-7; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3076)

SECTION 14. 329 IAC 4.1-2-8 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-2-8 "Nonmunicipal solid waste landfill" defined

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 8. "Nonmunicipal solid waste landfill" has the meaning as set forth at in 329 IAC 10-2-121. (Solid Waste Management Board; 329 IAC 4.1-2-8; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3076)

SECTION 15. 329 IAC 4.1-2-9 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-2-9 "Single location" defined

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 9. "Single location" means an aggregation of one (1) or more facilities that are:

- (1) located on:
 - (A) one (1) piece of property; or on
 - (B) contiguous or adjacent properties; and that are
- (2) owned or operated by the same person.

SECTION 16. 329 IAC 4.1-3-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-3-1 Conversion of federal terms

Authority: IC 13-20-15-1

Affected: IC 13-11-2-71; IC 13-20-15-6

- Sec. 1. When used in 40 CFR 264, Subpart D, and 40 CFR 761, as incorporated by reference in this article, substitute the following **federal terms are defined as provided in this section** unless otherwise indicated:
 - (1) "Act" means the environmental management laws as defined at IC 13-11-2-71.
 - (2) "Administrator" or "assistant administrator" means the commissioner of the Indiana department. of environmental management.
 - (3) "Agency" means the Indiana department. of environmental management.
 - (4) "Director", "director, chemical management division", or "director, CMD" means the commissioner of the Indiana department. of environmental management.
 - (5) "Environmental protection agency" or "EPA" means the Indiana department. of environmental management.
 - (6) "He" means he or she, without regard to gender.
 - (7) "Notification requirements of Section 3010" means the notification requirements of this article.
 - (8) "RCRA permit" means state hazardous waste permit.
 - (9) "Regional administrator" means the commissioner of the Indiana department. of environmental management.
 - (10) "She" means he or she, without regard to gender.
 - (11) "State", "authorized state", "approved state", and "approved program" means Indiana.
 - (12) "United States" means the state of Indiana.

(Solid Waste Management Board; 329 IAC 4.1-3-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3076)

SECTION 17. 329 IAC 4.1-4-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-4-1 Requirements for storage and disposal incorporated by reference

Authority: IC 13-20-15-1 IC 13-20-15-6

- Sec. 1. (a) 40 CFR 761, Subpart D, consisting of 40 CFR 761.50 through 40 CFR 761.79, is incorporated by reference, except as provided otherwise in section 2 of this rule.
- (b) 40 CFR 761, Subpart D is available for viewing and copying at the Office of Solid and Hazardous Waste Indiana Department of Environmental Management, Office of Land Quality, Indiana Government Center-North, 100 North Senate Avenue, Eleventh Floor West, Indianapolis, Indiana.
- (c) The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, 732 North Capitol Street NW, Washington, D.C. 20402. 20401. The telephone number for the Superintendent of Documents U.S. Government Printing Office is (202)

512-1800. **(202) 512-0000.** (Solid Waste Management Board; 329 IAC 4.1-4-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3076)

SECTION 18. 329 IAC 4.1-4-2 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-4-2 Exceptions and additions

Authority: IC 13-20-15-1

Affected: IC 13-20-15-6; 40 CFR 761, Subpart D

Sec. 2. **The** exceptions and additions to 40 CFR 761, Subpart D, are as follows:

- (1) Delete 40 CFR 761.60(b)(2)(iii)(B).
- (2) Delete 40 CFR 761.60(b)(2)(iv)(B).
- (3) Delete 40 CFR 761.60(b)(2)(v).
- (4) In 40 CFR 761.60(b)(2)(vi), delete "large PCB capacitors or".
- (5) Delete 40 CFR 761.60(f)(1)(iii).
- (6) In 40 CFR 761.65(b), delete "After July 1, 1978,".
- (7) Delete 40 CFR 761.65(d)(1).

(Solid Waste Management Board; 329 IAC 4.1-4-2; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3076)

SECTION 19. 329 IAC 4.1-5-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-5-1 PCB spill cleanup policy incorporated by reference

Authority: IC 13-20-15-1 IC 13-20-15-6

- Sec. 1. (a) 40 CFR 761, Subparts G and M through T are incorporated by reference, except as provided otherwise in section 2 of this rule.
- (b) 40 CFR 761, Subparts G and M through T are available for viewing and copying at the Indiana Department of Environmental Management, Office of Solid and Hazardous Waste Management, Land Quality, Indiana Government Center-North, 100 North Senate Avenue, Eleventh Floor West, Indianapolis, Indiana.
- (c) The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, 732 North Capitol Street NW, Washington, D.C. 20402. 20401. The telephone number for the Superintendent of Documents U.S. Government Printing Office is (202) 512-1800. (202) 512-0000. (Solid Waste Management Board; 329 IAC 4.1-5-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3077)

SECTION 20. 329 IAC 4.1-5-2 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-5-2 Exceptions and additions

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 2. **The** exceptions and additions to 40 CFR 761, Subparts G and M through T are as follows:

- (1) In 40 CFR 761.398(a), delete "the Director, National Program Chemicals Division (NPCD), (7404), Office of Pollution Prevention and Toxics, 401 M St., SW., Washington, DC" and substitute "the commissioner".
- (2) In 40 CFR 761.398(a), delete "From time to time, the Director of NPCD will confirm the use of validated new decontamination solvents and publish the new solvents and validated decontamination procedures in the Federal Register".

(Solid Waste Management Board; 329 IAC 4.1-5-2; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3077)

SECTION 21. 329 IAC 4.1-6-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-6-1 Requirements for PCB waste disposal records and reports incorporated by reference

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 1. (a) 40 CFR 761, Subpart K, consisting of 40 CFR 761.202 through 40 CFR 761.218, is incorporated by reference, except as provided otherwise in section 2 of this rule.
- (b) 40 CFR 761, Subpart K is available for viewing and copying at the Indiana Department of Environmental Management, Office of Solid and Hazardous Waste Management, Land Quality, Indiana Government Center-North, 100 North Senate Avenue, Eleventh Floor West, Indianapolis, Indiana.
- (c) The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, 732 North Capitol Street NW, Washington, D.C. 20402. 20401. The telephone number for the Superintendent of Documents U.S. Government Printing Office is (202) 512-1800. (202) 783-3238. (Solid Waste Management Board; 329 IAC 4.1-6-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3077)

SECTION 22. 329 IAC 4.1-6-2 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-6-2 Exceptions and additions

Authority: IC 13-20-15-1 IC 13-20-15-6

- Sec. 2. Exceptions and additions to 40 CFR 761, Subpart K, are as follows:
- (1) Delete 40 CFR 761.202(c).
- (2) In 40 CFR 761.205(a)(1), delete "April 4, 1990" and substitute a date six (6) months after the effective date of this article. with "February 13, 2001".
- (3) In 40 CFR 761.205(b), delete "April 4, 1990" and substitute a date six (6) months after the effective date of this article. with "February 13, 2001".
- (4) In 40 CFR 761.205(d), delete "Chief, Operations Branch (7404), Office of Pollution Prevention and Toxics, Environmental Protection Agency, 401 M St., SW, Washington, DC 20460" and substitute "Indiana Department of Environmental Management, Office of Solid and Hazardous Waste Management, P.O. Box 6015, Land Quality, 100 North Senate Avenue, MC 65-45, Indianapolis, Indiana 46206-6015". 46204-2251".
- (5) Delete 40 CFR 761.207(b). The manifest described in 329 IAC 3.1-7 and available from

the department must not be used for manifesting of PCB shipments. Generators may use copies of EPA Form 8700-22 from any other source to comply with this article.

(6) (5) In 40 CFR 761.202(b), delete "After June 4, 1990,".

(7) (6) In 40 CFR 761.211(a), delete "After April 4, 1990,".

(Solid Waste Management Board; 329 IAC 4.1-6-2; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3077)

SECTION 23. 329 IAC 4.1-7-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-7-1 Applicability

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 1. This rule applies to incinerators and high efficiency boilers **that are** required to be approved by the commissioner under 329 IAC 4.1-4-1, **that which** incorporates 40 CFR 761.60 and 40 CFR 761.70 by reference. (Solid Waste Management Board; 329 IAC 4.1-7-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3078)

SECTION 24. 329 IAC 4.1-7-2 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-7-2 General

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 2. Incinerators and high efficiency boilers must comply with **the provisions of** 329 IAC 4.1-4 through 329 IAC 4.1-6. (Solid Waste Management Board; 329 IAC 4.1-7-2; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3078)

SECTION 25. 329 IAC 4.1-7-3 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-7-3 Location restrictions

Authority: IC 13-20-15-1

Affected: IC 13-20-15-6; IC 36-7-4

- Sec. 3. (a) An incinerator or high efficiency boiler must comply with all **applicable** zoning and location restrictions of the political subdivision in which the facility is located. if any are imposed.
- (b) The owner or operator shall provide documentation that all required zoning and other local approvals, if any are required, have been obtained before written approval is requested under 329 IAC 4.1-4-1, that which incorporates 40 CFR 761.60 and 40 CFR 761.70 by reference, is requested. Documentation that all required zoning and other local approvals if any are required, have been obtained may include the following:
 - (1) A copy of the:
 - (A) zoning requirements, if any, for solid waste facilities in the area; where the facility is to be located.
 - (2) A copy of the (B) improvement location permit or occupancy permit issued by the zoning authority having jurisdiction for the site, if a solid waste land disposal facility

is permitted by the zoning ordinance in the area; where the facility is to be located. (3) A copy of the (C) amendment to the zoning ordinance adopted under IC 36-7-4-901 et seq., if:

- (i) a change in the zone maps is required for the area; where the facility is to be located. or
- (4) A copy of the amendment to the zoning ordinance adopted under IC 36-7-4-901 et seq., if (ii) such amendment is required for the area; where the facility is to be located. and
- (5) A copy of the (**D**) variance, special exception, special use, contingent use, or conditional use approved under IC 36-7-4-921 et seq., if such approval is required for the area;

where the facility is to be located.

- (6) (2) The status of any appeal of any zoning determination as described in subdivisions (2) subdivision (1)(B) through (5) (1)(D) and, if none is pending, the date by which the appeal must be initiated.
- (c) The owner or operator of an incinerator or high efficiency boiler shall not dredge or fill wetlands, except in compliance with an appropriate permit required by Section 404 of the Clean Water Act, as amended (33 U.S.C. 1344). (Solid Waste Management Board; 329 IAC 4.1-7-3; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3078)

SECTION 26. 329 IAC 4.1-7-4 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-7-4 Public notice and public participation

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 4. (a) Each applicant submitting a request for approval for an incinerator or high efficiency boiler under 329 IAC 4.1-4-1 shall submit a signed affidavit to the department agreeing to notify adjoining landowners with a notice as described in 329 IAC 10-12-1(b) and shall thereafter comply with the public notice and public participation requirements contained in 329 IAC 10-12-1 329 IAC 10-12-1(b) through 329 IAC 10-12-1(f), as follows:
 - (1) For an incinerator or high efficiency boiler for which construction was started prior to the effective date of this article, before August 13, 2000, the owner or operator shall comply with 329 IAC 10-12-1 329 IAC 10-12-1(b) through 329 IAC 10-12-1(f), before starting operation under this article.
 - (2) For an incinerator or high efficiency boiler for which construction is started on or after the effective date of this article, August 13, 2000, the owner or operator shall comply with 329 IAC 10-12-1 329 IAC 10-12-1(b) through 329 IAC 10-12-1(f), before beginning construction.
- (b) The department shall comply with 329 IAC 10-12-1(g) through 329 IAC 10-12-1(i) as appropriate after receipt of a request for approval under this section.
- (c) Failure of the applicant to comply with the requirements of this section may result in denial of the application by the commissioner. (Solid Waste Management Board; 329 IAC 4.1-7-4; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3078)

SECTION 27, 329 IAC 4.1-7-5 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-7-5 Notice of activity

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 5. (a) The owner or operator of an incinerator or high efficiency boiler shall notify the following at least thirty (30) days before beginning any storage, separation, processing, recovery, treatment, or disposal of waste containing PCBs:
 - (1) Indiana Department of Environmental Management, Office of Solid and Hazardous Waste Management, Land Quality, 100 North Senate Avenue, P.O. Box 6015, 100 North Senate Avenue, MC 65-45, Indianapolis, Indiana 46206-6015. 46204-2251.
 - (2) The:
 - (A) county health department; for the county in which the facility is located.
 - (3) The (B) emergency management director; and the
 - (C) local emergency planning committee;

for the county in which the facility is located.

- (4) (3) The fire department with jurisdiction over the facility.
- (b) Upon completion of any separation, processing, recovery, or treatment of PCB waste regulated under this article, the owner or operator of an incinerator or high efficiency boiler shall provide written notification to the department that the waste no longer contains PCBs. This notification must include either **of the following:**
 - (1) PCB disposal notification. or
- (2) Analytical documentation demonstrating that the PCBs were destroyed. (Solid Waste Management Board; 329 IAC 4.1-7-5; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3078)

SECTION 28. 329 IAC 4.1-8-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-8-1 Applicability

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 1. This rule applies to **a** chemical waste landfills **landfill** required to be approved by the commissioner under 329 IAC 4.1-4-1, that **which** incorporates 40 CFR 761.75(c) by reference. (Solid Waste Management Board; 329 IAC 4.1-8-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3079)

SECTION 29. 329 IAC 4.1-8-2 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-8-2 General

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 2. A chemical waste landfill must comply be in compliance with 329 IAC 4.1-4 through 329 IAC 4.1-6. (Solid Waste Management Board; 329 IAC 4.1-8-2; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3079)

SECTION 30. 329 IAC 4.1-8-3 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-8-3 Location restrictions

Authority: IC 13-20-15-1

Affected: IC 13-20-15-6; IC 36-7-4

Sec. 3. (a) A chemical waste landfill must comply with the location restrictions in 329 IAC 10-16 that apply to a new MSWLF or MSWLF unit permitted under 329 IAC 10, except that the reduction of setback distances in 329 IAC 10-16-12 does not apply to a chemical waste landfill.

- (b) The owner or operator **of a chemical waste landfill** shall provide documentation that all required zoning and other local approvals, if any are required, have been obtained before written approval is requested under 329 IAC 4.1-4-1, that which incorporates 40 CFR 761.75(c) by reference, is requested. Documentation that all required zoning and other local approvals if any are required, have been obtained may include the following:
 - (1) A copy of the:
 - (A) zoning requirements, if any, for solid waste facilities in the area; where the facility is to be located.
 - (2) A copy of the (B) improvement location permit or occupancy permit issued by the zoning authority having jurisdiction for the site, if a solid waste land disposal facility is permitted by the zoning ordinance in the area; where the facility is to be located.
 (3) A copy of the (C) amendment to the zoning ordinance adopted under IC 36-7-4-901 et seq., if:
 - (i) a change in the zone maps is required for the area; where the facility is to be located. or
 - (4) A copy of the amendment to the zoning ordinance adopted under IC 36-7-4-901 et seq., if (ii) such amendment is required for the area; where the facility is to be located. and
 - (5) A copy of the (**D**) variance, special exception, special use, contingent use, or conditional use approved under IC 36-7-4-921 et seq., if such approval is required for the area;

where the facility is to be located.

- (6) (2) The status of any appeal of any zoning determination as described in subdivisions (2) subdivision (1)(B) through (5) (1)(D) and, if none is pending, the date by which the appeal must be initiated.
- (c) The owner or operator of a chemical waste landfill shall not dredge or fill wetlands, except in compliance with an appropriate permit required by Section 404 of the Clean Water Act, as amended (33 U.S.C. 1344). (Solid Waste Management Board; 329 IAC 4.1-8-3; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3079)

SECTION 31, 329 IAC 4.1-8-4 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-8-4 Public notice and public participation

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 4. Each (a) An applicant submitting a request for approval for a chemical waste landfill under 329 IAC 4.1-4-1, that which incorporates 40 CFR 761.75(c) by reference, shall do the following:
 - (1) Submit a signed affidavit to the department agreeing to notify adjoining landowners with a notice as described in 329 IAC 10-12-1(b).
 - (2) Thereafter comply with the public notice and public participation requirements in 329 IAC 10-12-1. 329 IAC 10-12-1(b) through 329 IAC 10-12-1(f).
- (b) The department shall comply with 329 IAC 10-12-1(g) through 329 IAC 10-12-1(i) as appropriate after receipt of a request for approval under this section.
- (c) Failure of the applicant to comply with the requirements of this section may result in denial of the application by the commissioner. (Solid Waste Management Board; 329 IAC 4.1-8-4; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3079)

SECTION 32. 329 IAC 4.1-8-5 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-8-5 Notice of activity

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 5. (a) The owner or operator of a chemical waste landfill shall notify the following at least thirty (30) days before beginning any storage, separation, processing, recovery, treatment, or disposal of waste containing PCBs:
 - (1) Indiana Department of Environmental Management, Office of Solid and Hazardous Waste Management, Land Quality, 100 North Senate Avenue, P.O. Box 6015, MC 65-45, Indianapolis, Indiana 46206-6015. 46204-2251.
 - (2) The:
 - (A) county health department; for the county in which the facility is located.
 - (3) The (B) emergency management director; and the
 - (C) local emergency planning committee;

for the county in which the facility is located.

- (4) (3) The fire department with jurisdiction over the facility.
- (b) Upon completion of any separation, processing, recovery, or treatment of PCB waste regulated under this article, the owner or operator of a chemical waste landfill shall provide written notification to the department that the waste no longer contains PCBs. This notification must include either **of the following:**
 - (1) PCB disposal notification. or
- (2) Analytical documentation demonstrating that the PCBs were destroyed. (Solid Waste Management Board; 329 IAC 4.1-8-5; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3079)

SECTION 33. 329 IAC 4.1-9-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-9-1 Applicability

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6 Sec. 1. This rule applies to **an** alternative disposal facilities facility required to be approved under 329 IAC 4.1-4-1, that which incorporates 40 CFR 761.60(e) by reference. (Solid Waste Management Board; 329 IAC 4.1-9-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3080)

SECTION 34. 329 IAC 4.1-9-2 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-9-2 General

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 2. (a) The owner or operator of an alternative disposal facility must receive written approval by **from** the commissioner as follows:
 - (1) For an alternative disposal facility for which construction was started prior to the effective date of this article, before August 13, 2000, written approval must be received from the commissioner before starting operation under this article.
 - (2) For an alternative disposal facility for which construction is started on or after the effective date of this article, August 13, 2000, written approval must be received from the commissioner before beginning construction.
 - (b) The owner or operator of an alternative disposal facility shall **do the following:**
 - (1) Provide to the department a copy of the written approval from EPA required by 40 CFR 761.60(e).
 - (c) The owner or operator of an alternative disposal facility shall (2) Comply with the requirements of 329 IAC 4.1-4 through 329 IAC 4.1-6.

(Solid Waste Management Board; 329 IAC 4.1-9-2; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3080)

SECTION 35. 329 IAC 4.1-9-3 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-9-3 Location restrictions

Authority: IC 13-20-15-1

Affected: IC 13-20-15-6; IC 36-7-4

- Sec. 3. (a) An alternative disposal facility must comply with all **applicable** zoning and location restrictions of the political subdivision in which the facility is located. if any are imposed.
- (b) The owner or operator shall provide documentation that all required zoning and other local approvals, if any are required, have been obtained before written approval is requested under 329 IAC 4.1-4-1, that which incorporates 40 CFR 761.60(e) by reference, is requested. Documentation that all required zoning and other local approvals if any are required, have been obtained may include the following:
 - (1) A copy of the:
 - (A) zoning requirements, if any, for solid waste facilities in the area; where the facility is to be located.
 - (2) A copy of the (B) improvement location permit or occupancy permit issued by the zoning authority having jurisdiction for the site, if a solid waste land disposal facility is permitted by the zoning ordinance in the area; where the facility is to be located.

 (3) A copy of the (C) amendment to the zoning ordinance adopted under IC 36-7-4-

901 et seq., if:

- (i) a change in the zone maps is required for the area; where the facility is to be located. or
- (4) A copy of the amendment to the zoning ordinance adopted under IC 36-7-4-901 et seq.; if (ii) such amendment is required for the area; where the facility is to be located. and
- (5) A copy of the (**D**) variance, special exception, special use, contingent use, or conditional use approved under IC 36-7-4-921 et seq., if such approval is required for the area:

where the facility is to be located.

- (6) (2) The status of any appeal of any zoning determination as described in subdivisions (2) subdivision (1)(B) through (5) (1)(D) and, if none is pending, the date by which the appeal must be initiated.
- (c) The owner or operator of an alternative disposal facility shall not dredge or fill wetlands, except in compliance with an appropriate permit required by Section 404 of the Clean Water Act, as amended (33 U.S.C. 1344). (Solid Waste Management Board; 329 IAC 4.1-9-3; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3080)

SECTION 36. 329 IAC 4.1-9-4 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-9-4 Public notice and public participation

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 4. Each (a) An applicant submitting a request for approval of an alternative disposal facility under 329 IAC 4.1-4-1, that which incorporates 40 CFR 761.60(e) by reference, shall submit a signed affidavit to the department agreeing to notify adjoining landowners with a notice as described in 329 IAC 10-12-1(b) and shall thereafter comply with the public notice and public participation requirements in 329 IAC 10-12-1 329 IAC 10-12-1(b) through 329 IAC 10-12-1(f) as follows:
 - (1) For an alternative disposal facility for which construction was started prior to the effective date of this article, before August 13, 2000, the owner or operator shall comply with 329 IAC 10-12-1 329 IAC 10-12-1(b) through 329 IAC 10-12-1(f) before beginning:
 - (A) storage;
 - **(B)** separation;
 - (C) processing;
 - (D) recovery; or
 - (E) treatment;
 - of PCB waste under this article.
 - (2) For an alternative disposal facility for which construction is started on or after the effective date of this article, August 13, 2000, the owner or operator shall comply with 329 IAC 10-12-1 329 IAC 10-12-1(b) through 329 IAC 10-12-1(f) before beginning construction of the facility.
- (b) The department shall comply with 329 IAC 10-12-1(g) through 329 IAC 10-12-1(i) as appropriate after receipt of a request for approval under this section.

(c) Failure of the applicant to comply with the requirements of this section may result in denial of the application by the commissioner. (Solid Waste Management Board; 329 IAC 4.1-9-4; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3080)

SECTION 37. 329 IAC 4.1-9-5 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-9-5 Notice of activity

Authority: IC 13-20-15-1 IC 13-20-15-6

- Sec. 5. (a) The owner or operator of an alternative disposal facility shall notify the following at least thirty (30) days before beginning any storage, separation, processing, recovery, treatment, or disposal of waste containing PCBs:
 - (1) Indiana Department of Environmental Management, Office of Solid and Hazardous Waste Management, Land Quality, 100 North Senate Avenue, P.O. Box 6015, MC 65-45, Indianapolis, Indiana 46206-6015. 46204-2251.
 - (2) The:
 - (A) county health department; for the county in which the facility is located.
 - (3) The (B) emergency management director; and the
 - (C) local emergency planning committee;

for the county in which the facility is located.

- (4) (3) The fire department with jurisdiction over the facility.
- (b) Upon completion of any separation, processing, recovery, or treatment of PCB waste regulated under this article, the owner or operator of an alternative disposal facility shall provide written notification to the department that the waste no longer contains PCBs. This notification must include either **of the following:**
 - (1) PCB disposal notification. or
- (2) Analytical documentation demonstrating that the PCBs were destroyed. (Solid Waste Management Board; 329 IAC 4.1-9-5; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3080)

SECTION 38, 329 IAC 4.1-10-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-10-1 Mobile facilities

Authority: IC 13-20-15-1 IC 13-20-15-6

- Sec. 1. (a) A mobile facility that operates for one hundred eighty (180) days or less in a single location must comply with the following requirements:
 - (1) 40 CFR 761, Subpart D, incorporated by reference at 329 IAC 4.1-4-1.
 - (2) The requirements of 329 IAC 4.1-4 through 329 IAC 4.1-6, except the requirement to obtain approval from the commissioner under this article if the facility has obtained approval from the EPA under 40 CFR 761.60(e).
- (b) A mobile facility that operates for more than one hundred eighty (180) days in a single location must comply with the following requirements:
 - (1) 40 CFR 761, Subpart D, incorporated by reference at 329 IAC 4.1-4-1.

- (2) 329 IAC 4.1-4 through 329 IAC 4.1-6.
- (3) The mobile facility must comply with one (1) of the following:
 - (A) 329 IAC 4.1-7 for an incinerator or a high efficiency boiler.
 - (B) 329 IAC 4.1-8 for a chemical waste landfill.
 - (C) 329 IAC 4.1-9 for an alternative disposal facility.
- (4) The owner or operator of the mobile facility shall comply with the public notice and public participation requirements in 329 IAC 10-12-1 329 IAC 10-12-1(b) through 329 IAC 10-12-1(f) before continuing operations under this article.
- (5) The owner or operator of the mobile facility shall do the following:
 - (A) Submit a signed affidavit to the department agreeing to notify adjoining landowners with a notice as described in 329 IAC 10-12-1(b).
 - (B) Thereafter comply with the public notice and public notice and public participation requirements in 329 IAC 10-12-1(b) through 329 IAC 10-12-1(f).
- (6) The department shall comply with 329 IAC 10-12-1(g) through 329 IAC 10-12-1(i) as appropriate after receipt of a request for approval under this section.
- (7) Failure of the applicant to comply with the requirements of this section may result in denial of the application by the commissioner.
- (c) The owner or operator of a mobile facility shall do the following:
- (1) Provide to the department a copy of the written approval from EPA.
- (2) Notify the following at least thirty (30) days before beginning an activity regulated under this article:
 - (A) Indiana Department of Environmental Management, Office of Solid and Hazardous Waste Management, Land Quality, 100 North Senate Avenue, P.O. Box 6015, MC 65-45, Indianapolis, Indiana 46206-6015. 46204-2251.
 - (B) The county health department for the county in which the activity takes place.
 - (C) The emergency management director and the local emergency planning committee for the county in which the facility is located.
 - (D) The fire department with jurisdiction over the facility.
- (d) Upon completion of an activity regulated under this article, the owner or operator of a mobile facility shall provide written notification to the department that the waste no longer contains PCBs. This notification must include either **of the following:**
 - (1) PCB disposal notification. or
- (2) Analytical documentation demonstrating that the PCBs were destroyed. (Solid Waste Management Board; 329 IAC 4.1-10-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3081)

SECTION 39. 329 IAC 4.1-11-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-11-1 Incorporation by reference; contingency plan

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 1. (a) 40 CFR 264, Subpart D, consisting of 40 CFR 264.50 through 40 CFR 264.56, is incorporated by reference, except as provided in subsection (d).
 - (b) 40 CFR 264, Subpart D is available for viewing and copying at the Office of Solid and

Hazardous Waste Management, Land Quality, Indiana Government Center-North, Eleventh Floor West, 100 North Senate Avenue, Indianapolis, Indiana.

- (c) The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, 732 North Capitol Street NW, Washington, D.C. 20402. 20401. The telephone number for the Superintendent of Documents U.S. Government Printing Office is (202) 512-1800. (202) 512-0000.
- (d) Delete 40 CFR 264.50. (Solid Waste Management Board; 329 IAC 4.1-11-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3081)

SECTION 40. 329 IAC 4.1-11-2 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-11-2 Contingency plan

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 2. (a) The owner or operator of:

- (1) an incinerator or high efficiency boiler;
- (2) a chemical waste landfill;
- (3) an alternative disposal facility; or
- (4) a mobile facility;

shall prepare and maintain a contingency plan in accordance with 40 CFR 264.51 through 40 CFR 264.54.

- (b) The contingency plan must be as follows:
- (1) be Designed to minimize hazards to human health and the environment from any of the following:
 - (A) Fires.
 - (B) Explosions. or
 - (C) Any unplanned sudden or nonsudden release of PCB waste to any of the following:
 - (i) Air.
 - (ii) Soil.
 - (iii) Surface water. or
 - (iv) Ground water. and
- (2) Meet the requirements of 40 CFR 264.51 through 40 CFR 264.54.
- (c) The A person required to prepare a contingency plan shall provide copies of the contingency plan to the:
 - (1) local emergency planning committee; and
 - (2) the emergency management director;

for the county in which the facility is located before operation of the facility begins. (Solid Waste Management Board; 329 IAC 4.1-11-2; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3082)

SECTION 41. 329 IAC 4.1-11-3 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-11-3 Use of contingency plan

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 3. The **An** owner or operator of a facility described in section 2(a) of this rule shall carry out the provisions of the contingency plan immediately whenever there is:
 - (1) a fire;
 - (2) an explosion; or
 - (3) a release of PCB waste;

that could threaten human health or the environment. (Solid Waste Management Board; 329 IAC 4.1-11-3; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3082)

SECTION 42. 329 IAC 4.1-11-4 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-11-4 Emergency coordinator

Authority: IC 13-20-15-1 IC 13-20-15-6

- Sec. 4. (a) The **An** owner or operator of a facility described in section 2(a) of this rule shall designate an employee as the emergency coordinator as required in 40 CFR 264.55.
- (b) The emergency coordinator shall carry out the duties described in 40 CFR 264.56 that are appropriate for the facility. (Solid Waste Management Board; 329 IAC 4.1-11-4; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3082)

SECTION 43. 329 IAC 4.1-12-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-12-1 General

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 1. Owners An owner or operators operator of the following types of facilities shall comply with the financial assurance requirements in 329 IAC 3.1-15:
 - (1) An incinerator or high efficiency boiler.
 - (2) A chemical waste landfill.
 - (3) An alternative disposal facility.

(Solid Waste Management Board; 329 IAC 4.1-12-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3082)

SECTION 44, 329 IAC 4.1-13-1 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-13-1 Disposal in MSWLF units or nonmunicipal solid waste landfill units

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 1. (a) A person who disposes of waste containing or contaminated with PCBs in a MSWLF unit or a nonmunicipal solid waste landfill unit shall comply with all **applicable** requirements of

- (1) 40 CFR 761, Subpart D, as incorporated by reference at 329 IAC 4.1-4. and
- (2) 329 IAC 10-8.1 **329 IAC 10, and**
- (3) this rule.
- (b) In addition to the requirements of subsection (a), person who disposes of any waste containing PCBs in a MSWLF unit that does not meet the design requirements of 329 IAC 10-17 or a nonmunicipal solid waste landfill shall:
 - (1) obtain written authorization from the commissioner prior to disposal of any quantity of the waste; and
 - (2) comply with any conditions in the written authorization by the commissioner.
- (c) In addition to the requirements of subsection (a), person who disposes of a waste listed in Table 1 in a MSWLF unit that meets the design requirements of 329 IAC 10-17 shall:
 - (1) obtain written authorization from the commissioner prior to disposal of any quantity of the waste; and
 - (2) comply with any conditions in the written authorization by the commissioner.

Table 1.

Waste that contains PCBs at a concentration less than 50 ppm PCBs, resulting from a source that had a PCB concentration greater than or equal to 50 ppm PCBs.

Items or wastes containing inadvertently generated PCBs.

- (d) Instead of following the requirements of subsections (a) through (c) of this section, a person who disposes of a waste that contains PCBs at a concentration of less than fifty (50) parts per million resulting from a source that had a PCB concentration less than fifty (50) parts per million PCBs in a MSWLF unit or a nonmunicipal solid waste landfill unit shall provide a signed letter to the landfill stating that the PCB concentration in the source was less than fifty (50) parts per million PCBs.
- (e) Fluorescent light ballasts containing PCBs that are leaking or no longer intact must be disposed of in accordance with 40 CFR 761.62(a) or 40 CFR 761.62(c).
 - (f) Nonleaking fluorescent light ballasts containing PCBs must be disposed of as follows:
 - (1) Dispose of the ballasts only in a MSWLF unit that meets the design requirements of 329 IAC 10-17.
 - (2) Place the ballasts in a container that meets the packaging requirements in 40 CFR 761.60(b)(2)(iv) as incorporated by reference in 329 IAC 4.1-4.
 - (3) Fill the interstitial space in the container with absorbent material capable of absorbing all liquid content of the ballasts and capacitors.
 - (4) Segregate containers of fluorescent light ballasts from organic liquids disposed of in the landfill unit.
 - (5) Before compacting with heavy equipment, cover containers of fluorescent light ballasts with a layer of:
 - (A) daily cover material;
 - (B) alternative daily cover material; or
 - (C) solid waste;

that is thick enough to prevent crushing of the containers.

(6) Collect leachate from the landfill unit and monitor the leachate for PCBs.

- (7) Comply with all applicable requirements of 329 IAC 10-8.1.
- (g) Nonleaking fluorescent light ballasts containing PCBs must not be disposed of in a MSWLF unit that does not meet the design requirements of 329 IAC 10-17. (Solid Waste Management Board; 329 IAC 4.1-13-1; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3082; errata filed Jul 14, 2000, 10:59 a.m.: 23 IR 3091)

SECTION 45. 329 IAC 4.1-13-2 IS AMENDED TO READ AS FOLLOWS:

329 IAC 4.1-13-2 Disposal in other solid waste land disposal facilities

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 2. Any wastes containing or contaminated with PCBs must not be disposed of in:
- (1) a construction/demolition site as defined at 329 IAC 10-2-36; or
- (2) a restricted waste site as defined at 329 IAC 10-2-159.

(Solid Waste Management Board; 329 IAC 4.1-13-2; filed Jul 14, 2000, 11:09 a.m.: 23 IR 3083)

SECTION 46. 329 IAC 4.1-13-3 IS ADDED TO READ AS FOLLOWS:

329 IAC 4.1-13-3 Disposal of waste containing PCBs; state authorization

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 3. (a) This section does not apply to the disposal of PCB household waste, as defined at 40 CFR 761.3.
- (b) <u>As follows.</u> If the requirements of section 1 of this rule do not include a requirement for approval by the U.S. EPA Regional Administrator before disposal of a <u>specific PCB</u> waste, then:
 - (1) in addition to compliance with the requirements of section 1 of this rule, a person who disposes of any waste containing PCBs in a MSWLF unit that does not meet the design requirements of 329 IAC 10-17 or in a nonmunicipal solid waste landfill that is not specifically permitted to accept the waste shall do the following:
 - $\frac{(A)}{(1)}$ Obtain written authorization from the commissioner before disposal of any quantity of the waste.
 - (B)(2) Comply with any conditions for disposal in the written authorization by the commissioner.
 - (2)(c) If the requirements of section 1 of this rule do not include a requirement for approval by the U.S. EPA Regional Administrator before disposal of a PCB waste, then in addition to compliance with the requirements of section 1 of this rule, a person who disposes of a waste listed in Table 1 in a MSWLF unit that meets the design requirements of 329 IAC 10-17, or in a non-municipal solid waste landfill permitted to accept the PCB waste, shall do the following:
 - (A) Obtain written authorization from the commissioner before disposal of any quantity of the waste.
 - (B) Comply with any conditions for disposal in the written authorization by the

Table 1.

Waste that contains PCBs at a concentration less than fifty (50) ppm PCBs, resulting from a source that had a PCB concentration greater than or equal to fifty (50) ppm PCBs.

Items or wastes containing inadvertently generated PCBs.

(Solid Waste Management Board; 329 IAC 4.1-13-1)

SECTION 47. 329 IAC 4.1-13-4 IS ADDED TO READ AS FOLLOWS:

329 IAC 4.1-13-4 Disposal of PCB wastes; notification to landfills

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

- Sec. 4. A person who disposes of a waste that contains PCBs at a concentration of less than fifty (50) parts per million resulting from a source that had a PCB concentration less than fifty (50) parts per million PCBs in a:
 - (1) MSWLF; or
- (2) nonmunicipal solid waste landfill, permitted to accept the PCB waste; <u>unit</u> shall provide a written and signed notification to the landfill stating that the PCB concentration in the source was less than fifty (50) parts per million PCBs. (Solid Waste Management Board; 329 IAC 4.1-13-4)

SECTION 48. 329 IAC 4.1-13-5 IS ADDED TO READ AS FOLLOWS:

329 IAC 4.1-13-5 Disposal of fluorescent light ballasts containing PCBs

Authority: IC 13-20-15-1 Affected: IC 13-20-15-6

Sec. 5. (a) Fluorescent light ballasts containing PCBs that are:

- (1) leaking; or
- (2) no longer intact;

must be disposed of in accordance with 40 CFR 761.62(a) or 40 CFR 761.62(c).

- (b) Nonleaking fluorescent light ballasts containing PCBs must be disposed of as follows:
 - (1) Dispose of the ballasts only in a MSWLF unit that meets the design requirements of 329 IAC 10-17.
 - (2) Place the ballasts in a container that meets the packaging requirements in 40 CFR 761.60(b)(2)(iv) as incorporated by reference in 329 IAC 4.1-4.
 - (3) Fill the interstitial space in the container with absorbent material capable of absorbing all liquid content of the ballasts and capacitors.
 - (4) Segregate containers of fluorescent light ballasts from organic liquids disposed of in the landfill unit.
 - (5) Before compacting with heavy equipment, cover containers of fluorescent light ballasts with a layer of:
 - (A) daily cover material;

- (B) alternative daily cover material; or
- (C) solid waste;

that is thick enough to prevent crushing of the containers.

- (6) Collect leachate from the landfill unit and monitor the leachate for PCBs.
- (c) Nonleaking fluorescent light ballasts containing PCBs must not be disposed of in a MSWLF unit that does not meet the design requirements of 329 IAC 10-17. (Solid Waste Management Board; 329 IAC 4.1-13-5)